



Material Technologies

For Rubber, Plastics, Adhesives, Sealants & Specialty Coatings

ALBEMARLE

SAYTEX® Brominated FR

AMG ANTIMONY

HTS Antimony Trioxide

ARCLIN

KEVLAR® Aramid Pulp and Staple

ARLANXEO KELTAN KSA PERFORMANCE POLYMERS

EPDM Ethylene-Propylene Rubber

BIRLA CARBON

ASTM Carbon Blacks

EP Enhanced Performance Carbon Black

ULTRA® Rubber Blacks

BUDENHEIM USA, INC.

Phosphorus & Nitrogen Flame Retardants

CHASE CORPORATION

DUALITE® E Polymeric Microspheres

DUALITE® U Polymeric Microspheres

CHEM-TREND

MONO-COAT® Mold Release Agents

CHEM-TREND PM® Mold Release Agents

IPMC-1200 Mold Cleaner

CNG FILMS

Cast Embossed PE Films

DOW CHEMICAL

MOR-FLOCK® Flocking Adhesives

DRASNER

LOMEL® Low Melt Batch Inclusion Bags

DUPONT

Specialty Adhesives & Polymers

DUPONT TRANSPORTATION & INDUSTRIAL

THIXON® Solvent-Based Adhesives

MEGUM® Solvent Based Adhesives

MEGUM W® Water-Based Adhesives

ELKEM MATERIALS

SIDISTAR® Silicon Dioxide

EVERHARD®

EVERHARD® Roller & Stitchers

H&R GROUP, US, INC.

Tudalen® Paraffinic Oils

Tudalen® Aromatic Oils

HEXPOL COMPOUNDING

PROFLEX® NBR/PVC

HOLLAND COLOURS

Holcosil® LSR & RTV Silicone Colorant

KETTLITZ

KEZADOL Surface Coated Calcium Oxide

SILANOGRAN Silane Granulate

MEDIAPLAST Low Polarity Plasticizer

HAFTOLAT EPM Process Aid

LAWTER, INC.

FILTREZ® Resins Modified Maleic Resin

MAGRIS TALC

MISTRON® Talc

MARTIN MARIETTA

ELASTOMAG® Magnesium Oxide

MAGSHIELD® Magnesium Hydroxide

NORAC

NORSTAB® Ca/Zn Heat Stabilizers

COAD® Metallic Stearates

LIGOPHOB Sodium Soaps

LIGOSTAR Metallic Soaps

Ester Lubricants & Blends

NOURYON POLYMER CATALYST

PERKADOX® Organic Peroxides

TRIGONOX® Organic Peroxides

KETJENBLACK® Conductive Carbon Black

NOURYON - Expancel Spheres

Expancel® Blowing Agents

PAMPA ENERGIA

Arpol® SBR

PERFORMANCE CHEMICALS, LLC

CALZIN® Strip & Slab Dip

PROAMPAC

DARTEK® Cure Wrap Tape

DARTEK® Composite Film

RAIN CARBON, INC.

NOVARES® C9 Hydrocarbon Resins

NOVARES® C-I Resins

NOVARES® Liquid Modifying Resins

RUETASOLV® High Boiling Point Solvent

RJ MARSHALL

H-TEC™ ATH

C-TEC™ Zinc Stannate

C-TEC™ Zinc Borate

ROYAL

ARAMID BLEND – ROY-TUFF™

RHEOMETER Test Film

ROY CAL H Ground Oyster Shell

RUBBERMAKERS Sulfur

ROYAL BRANDED CLAYS-HARD & SOFT

SAN JUAQUIN REFINING

RAFFEX® Aromatic Process Oils

RAFFEN E® Napthenic Process Oils

HYNAP® Hydrotreated Napthenic Oils

SHIRAIISHI CALCIUM

VISCOLITE® Precipitated Calcium Carbonate

HAKUENKA® Precipitated Calcium

Carbonate VISCOEXCE® Precipitated Calcium Carbonate

SIGMA GROUP (Omega)

Smooth Blown PE Film

SILKIMYA

REFORSI® Precipitated Silica

SONNEBORN

SONNEBORN® Petrolatum

SPECIALTY MINERALS

Dry & Wet Ground Calcium Carbonate

THE INTERNATIONAL GROUP

IGI Paraffin Wax

TOKUYAMA

REOLOSIL® Fumed Silica

TORAY

THIOKOL® Liquid Polysulfide

CTPI® Cure Retarder

TRI-Iso TRYLINE

Titanium Dioxide

TRM MANUFACTURING

Blown Smooth PE Film

WACKER CHEMICAL CORPORATION

ELASTOSIL® HCR Solid Silicone Rubber

ELASTOSIL® LSR Liquid Silicone Rubber

ELASTOSI® RTV 2 Silicone Rubber

SILPURAN® Medical Grade Silicone

ZOCHEM, INC.

French Press Zinc Oxide

PARTICLE SIZE CONVERSION TABLE						
SEIV E	MES	H ¹ MICRON	MILLI- METE R	INCH	MIL	HEGMAN FINENESS
		0.0	0.000	0.0000	0.00	8.0
		6.4	0.006	0.0003	0.25	7.5
1200		10.2	0.010	0.0004	0.40	
		12.7	0.127	0.0005	0.50	7.0
		19.1	0.019	0.0008	0.75	6.5
625		20.3	0.020	0.0008	0.80	
		25.4	0.025	0.0010	1.00	6.0
		30.5	0.031	0.0012	1.20	
		31.8	0.032	0.0125	1.25	5.5
400		38.1	0.038	0.0015	1.50	5.0
		40.6	0.041	0.0016	1.60	
325		44.5	0.045	0.0018	1.75	4.5
		50.8	0.051	0.0020	2.00	4.0
270		53.3	0.053	0.0021	2.10	
		57.2	0.057	0.0023	2.25	3.5
230		61.0	0.061	0.0024	2.40	
		63.5	0.064	0.0025	2.50	3.0
		69.9	0.070	0.0028	2.75	2.5
		71.1	0.071	0.0028	2.80	
200		73.7	0.074	0.0029	2.90	
		76.2	0.076	0.0030	3.00	2.0
		81.3	0.081	0.0032	3.20	
		82.6	0.083	0.0033	3.25	1.5
170		88.9	0.089	0.0035	3.50	1.0
		95.3	0.095	0.0038	3.75	0.5
140		101.6	0.102	0.0040	4.00	0.0
120		125.0	0.125	0.0049	4.90	
100		149.0	0.149	0.0059	5.90	
80		177.0	0.177	0.0070	7.00	
70		210.0	0.210	0.0083	8.30	

1) STANDARD SIEVE MESH: ASTM E 11-81/ISO 565. The sieve numbers are the approximate number of openings per linear inch.
2) HEGMAN FINENESS: ASTM D 1210-96. Fineness of dispersion of pigment-vehicle systems by Hegman-type gage.

SIZE & SCALE			
NAME	SYMBOL	VALUE	EQUIVALENT (in METERS)
picometer	pm	10 ⁻¹²	0.000 000 000 001
nanometer	nm	10 ⁻⁹	0.000 000 001
micrometer	µm	10 ⁻⁶	0.000 001
millimeter	mm	10 ⁻³	0.001
centimeter	cm	10 ⁻²	0.01
decimeter	dm	10 ⁻¹	0.1
meter	m	1	1
decameter	dam	10	10
hectometer	hm	10 ²	100
kilometer	km	10 ³	1 000
megameter	Mm	10 ⁶	1 000 000
gigameter	Gm	10 ⁹	1 000 000 000
tetrameter	Tm	10 ¹²	1 000 000 000 000

CONVERSION FORMULAS

Mass

1 Metric Ton (t)	=	2204.6 pounds	lb
1 Metric Ton (t)	=	1000 kilograms	kg
1 kilogram (kg)	=	2.205 pounds	lb
1 pound (lb)	=	0.454 kilograms	kg
1 Short Ton (tn)	=	2,000 pounds	lb

Length

1 meter (m)	=	39.37 inches	in
1 meter (m)	=	3.281 feet	ft
1 mil	=	25.4 micron	µm

Temperature

$$^{\circ}\text{C} = (^{\circ}\text{F} - 32) / 1.8$$

$$^{\circ}\text{F} = (^{\circ}\text{C} * 1.8) + 32$$

SPECIFIC GRAVITY/DENSITY CONVERSION

g/cc	1	1000	8.3454	62.43
kg/m ³	0.0010	1	0.0083	0.0624
lbs/gal	0.1198	119.83	1	7.4805
lbs/cu-ft	0.0160	16.018	0.1337	1
	g/cc	kg/m ³	lbs/gal	lbs/cu-ft

Read across, then down. Example, 1 g/cc (red column) = 1000 (2nd numeric column) kg/m³ (blue bottom header). NOTE: cm³ = g/cc

HARDNESS SCALES COMPARISON

SHORE A	20	30	40	50	60	70	80	90	95										
SHORE D								45	55	65	75	85							
ROCKWELL R								50	70	90	100	110	110	120	130	140	150		

POLYMERS

by Decreasing Polarity

Polymer	Abbr.
MORE POLAR	
Nylon	PA
Polysulfide	T
Polyurethane	PU
Nitrile (High ACN)	NBR
Epoxy	EP
Polycarbonate	PC
Polyvinyl Acetate	PVA
Nitrile (Med ACN)	NBR
Acrylic Rubber	ACM
Epichlorohydrin	ECO
Chlorosulfonated	CSM
Polyvinyl Chloride	PVC
Polystyrene	PS
Polychloroprene	CR
Nitrile (Low ACN)	NBR
Chlorinated PE	CPE
Styrene-Butadiene Rubber	SBR
Polybutadiene	BR
Natural Rubber	NR
Halo Butyl	HIIR
Ethylene-Propylene Diene	EPDM
Ethylene-Propylene Rubber	EPR
Butyl Rubber	IIR
Fluoroelastomer	FKM
Silicone	Q
LESS POLAR	

TEMP	
°C	°F
538	1000
	500
482	900
	475
	450
427	800
	425
	400
	375
371	700
	350
	325
316	600
	300
	275
260	500
	250
232	450
	225
204	400
	200
191	375
177	350
	175
163	325
	150
149	300
135	275
	125
121	250
	100
38	100
	21
	10
	0
-4	25
	-10
-12	10
-18	0
	-25
-32	-25
-46	-50
	-50
-73	-100
	-100
-157	-250
	-200
	-273
	-460